The CAB

General Information, Standard Equipment

	The CAB	CAB XL
- Lenght	5.75 meter	7.25 meter
- Width	2.13 meter	2.34 meter
- Height	1.05 meter	1.28 meter
- Draught	0.60 meter	0.75 meter
- Displacement, construction weight	1100 kg	1800 kg
Duefe e alemated alemates Mentine de Tenen V		_

- Professional design by Martin de Jager Yachtdesign
- CE-certified according to EG directives 94/25/EEG Cat. C 8 pers.
- Canopy on aluminium frame with aft cover in blue or black Markilux
- Full cushionset in the cockpit, seat and back, front and aft
- Off-white polyester hull with a darkblue edge
- Optional choice of 32 colours/combinations
- Fully 100% hand-layup, no spray-gun
- Unsinkable by blocks of Polystyreen
- Floorpanels in the colour of the edge with anti slip profile
- Sleeping facilities (in combination with a sundeck)
- Front- en backbenches with good backsupport
- Big storage capacity in all benches in the front and the back.
- Very width entrance steps with on both sides storage capacity
- Steering column with a teak STAZO steeringwheel
- Gangway of massive teak, 80 * 11 mm
- Massive teak edge around the benches 50 * 12 mm
- Massive teak fenderlist (50 * 10 mm) on cockpit coaming
- Teak on the enginebox with massive edges and fiddles
- Massive teak on the afthatch
- Teak fenderlist around the ship 25 * 12 mm
- Teak decking on the aft hatch 30 * 25 mm
- Vetus 16 PK 2-cilinder diesel, intercooler
- Hydraulic steering mechanism
- Waterlubricated shaft systeem
- Bullflex flexibele coupling
- Manual bilgepomp RM 69J
- Heavy sound & vibration insulation
- 55 Ah maintenaincefree battery
- 45 liter fueltank
- RPM & hour-counter
- White steam light (sufficient for innerwaters)
- Ssteel 316 (seawater proof) cleats, clamps, hinges etc.
- Ssteel 316 flagholder
- Ssteel 316 rudderfittings and keelshoe
- Antifouling (AKZO-Sikkens 2000) below waterline