

NEIL MARINE

27 FT. SPORTS FISHING/DIVE EXCURSION CATAMARAN

HULL-FIBRE GLASS HULL REINFORCED WITH POLY URETHANE FOAM TRANSVERSE FRAMES AND LONGITUDINALS GLASSED

DECK -FIBRE GLAS DECK WITH MOULDED NONSKID SURFACE REINFOCED Balsa CORE SANDWITCH CONSTRUCTION

MOULDED WITH ISOPHTHALIC GELCOAT AND RESIN USING ONLY LLOYDS REGISTER OF SHIPPING (UK) OR INTERNATIONAL ASSOCIATION OF CLASSIFICATION SOCIETIES MEMBER TYPE APPROVED MARINE GRADE FIBRE GLASS MATERIAL



BOAT SPECIFICATION

Length Overall	8.5 Meters. (27.8 Feet)
Beam	2.3 Meters. (7.5 Feet)
Draft(Unladen)	0.3 Meters (11 inches)
Displacement	2100 KG.
Persons	08 Persons
Engines	2 x 250 HP OBM
Speed	25 Knots
Fuel Capacity	2 x 250 Liters.
Fresh Water Capacity	150 Liters.
Seating Capacity	08 Persons

Vessel Lay Out

Fore peak anchor locker provided with deck access hatches fitted on deck.

Fwd. Cabin is fitted with a Double berth to starboard and an enclosed toilet compartment provided to port with a Marine WC and a wash basin fitted with a freshwater tap

Wheelhouse fitted with large windows for all round visibility. Helm position provided to starboard front fitted with a helmsman seat and consist of a console fitted with steering wheel, OBM controls and instrumentation.

An insulated ice box fitted aft of helmsman with extra seating provided to port.

02 nos. Insulated fish boxes fitted under the fwd. cockpit with flush access hatches on deck.

02 nos. fuel tanks are positioned under aft cockpit flooring.

Bait well of 70 liters capacity is fitted to aft port and a storage box to starboard to stern.

02 nos. inspection hatches fitted on outboard transom well for maintenance and inspection.

12 Volts DC main electrical system consist of two battery banks of 2 x 120 Amp each for engine start and lighting & equipment. Lighting consist of standard vessel lights and navigation lights.

Life buoys and life jackets

Navigational and Communication Equipment supplied as per customer requirement

.Mooring Bollards fitted on Fwd. and Aft. Decks.

